

PRESIDIO MILITARY SPECIFICATION PART NUMBERS

CDR11 AND CDR12 — MIL-PRF-55681

CAPACITOR CHARACTERISTICS — SIZE 0505

Type Designation	Capacitance (pF)	Cap. Tolerance	Rated Temp. & Voltage-Temp. Limits	Rated Voltage (V dc)
CDR1-BP0R1-B -	0.1	B	BP	50, 150
CDR1-BP0R2-B -	0.2	B	BP	50, 150
CDR1-BP0R3 -	0.3	B, C	BP	50, 150
CDR1-BP0R4 -	0.4	B, C	BP	50, 150
CDR1-BP0R5 -	0.5	B, C, D	BP	50, 150
CDR1-BP0R6 -	0.6	B, C, D	BP	50, 150
CDR1-BP0R7 -	0.7	B, C, D	BP	50, 150
CDR1-BP0R8 -	0.8	B, C, D	BP	50, 150
CDR1-BP0R9 -	0.9	B, C, D	BP	50, 150
CDR1-BP1R0 -	1	B, C, D	BP	50, 150
CDR1-BP1R1 -	1.1	B, C, D	BP	50, 150
CDR1-BP1R2 -	1.2	B, C, D	BP	50, 150
CDR1-BP1R3 -	1.3	B, C, D	BP	50, 150
CDR1-BP1R4 -	1.4	B, C, D	BP	50, 150
CDR1-BP1R5 -	1.5	B, C, D	BP	50, 150
CDR1-BP1R6 -	1.6	B, C, D	BP	50, 150
CDR1-BP1R7 -	1.7	B, C, D	BP	50, 150
CDR1-BP1R8 -	1.8	B, C, D	BP	50, 150
CDR1-BP1R9 -	1.9	B, C, D	BP	50, 150
CDR1-BP2R0 -	2	B, C, D	BP	50, 150
CDR1-BP2R1 -	2.1	B, C, D	BP	50, 150
CDR1-BP2R2 -	2.2	B, C, D	BP	50, 150
CDR1-BP2R4 -	2.4	B, C, D	BP	50, 150
CDR1-BP2R7 -	2.7	B, C, D	BP	50, 150
CDR1-BP3R0 -	3	B, C, D	BP	50, 150
CDR1-BP3R3 -	3.3	B, C, D	BP	50, 150
CDR1-BP3R6 -	3.6	B, C, D	BP	50, 150
CDR1-BP3R9 -	3.9	B, C, D	BP	50, 150
CDR1-BP4R3 -	4.3	8, C, D	BP	50, 150
CDR1-BP4R7 -	4.7	B, C, D	BP	50, 150
CDR1-BP5R1 -	5.1	B, C, D	BP	50, 150
CDR1-BP5R6 -	5.6	B, C, D	BP	50, 150
CDR1-BP6R2 -	6.2	B, C, D	BP	50, 150
CDR1-BP6R8 -	6.8	B, C, J, K, M	BP	50, 150
CDR1-BP7R5 -	7.5	B, C, J, K, M	BP	50, 150
CDR1-BP8R2 -	8.2	B, C, J, K, M	BP	50, 150
CDR1-BP9R1 -	9.1	B, C, J, K, M	BP	50, 150
CDR1-BP100 -	10	F, G, J, K, M	BP	50, 150
CDR1-BP110 -	11	F, G, J, K, M	BP	50, 150
CDR1-BP120 -	12	F, G, J, K, M	BP	50, 150
CDR1-BP130 -	13	F, G, J, K, M	BP	50, 150
CDR1-BP150 -	15	F, G, J, K, M	BP	50, 150
CDR1-BP160 -	16	F, G, J, K, M	BP	50, 150

SPACE LEVEL 'S'					DLA DWG 06022	
Type Designation	Capacitance (pF)	Cap. Tolerance	Rated Temp. & Voltage-Temp. Limits	Rated Voltage (V dc)		
CDR1-BP180 -	18	F, G, J, K, M	BP	50, 150		
CDR1-BP200 -	20	F, G, J, K, M	BP	50, 150		
CDR1-BP220 -	22	F, G, J, K, M	BP	50, 150		
CDR1-BP240 -	24	F, G, J, K, M	BP	50, 150		
CDR1-BP270 -	27	F, G, J, K, M	BP	50, 150		
CDR1-BP300 -	30	F, G, J, K, M	BP	50, 150		
CDR1-BP330 -	33	F, G, J, K, M	BP	50, 150		
CDR1-BP360 -	36	F, G, J, K, M	BP	50, 150		
CDR1-BP390 -	39	F, G, J, K, M	BP	50, 150		
CDR1-BP430 -	43	F, G, J, K, M	BP	50, 150		
CDR1-BP470 -	47	F, G, J, K, M	BP	50, 150		
CDR1-BP510 -	51	F, G, J, K, M	BP	50, 150		
CDR1-BP560 -	56	F, G, J, K, M	BP	50, 150		
CDR1-BP620 -	62	F, G, J, K, M	BP	50, 150		
CDR1-BP680 -	68	F, G, J, K, M	BP	50, 150		
CDR1-BT750 -	75	F, G, J, K, M	BP	50, 150		
CDR1-BP820 -	82	F, G, J, K, M	BP	50, 150		
CDR1-BP910 -	91	F, G, J, K, M	BP	50, 150		
CDR1-BP101 -	100	F, G, J, K, M	BP	50, 150		
CDR1-BP111 -	110	F, G, J, K, M	BP	50, 100		
CDR1-BP121 -	120	F, G, J, K, M	BP	50, 100		
CDR1-BP131 -	130	F, G, J, K, M	BP	50, 100		
CDR1-BP151 -	150	F, G, J, K, M	BP	50, 100		
CDR1-BP161 -	160	F, G, J, K, M	BP	50, 100		
CDR1-BP181 -	180	F, G, J, K, M	BP	50, 100		
CDR1-BP201 -	200	F, G, J, K, M	BP	50, 100		
CDR1-BP221 -	220	F, G, J, K, M	BP	50, 100		
CDR1-BP241 -	240	F, G, J, K, M	BP	50, 100		
CDR1-BP271 -	270	F, G, J, K, M	BP	50, 100		
CDR1-BP301 -	300	F, G, J, K, M	BP	50, 100		
CDR1-BP331 -	330	F, G, J, K, M	BP	50, 100		
CDR1-BP361 -	360	F, G, J, K, M	BP	50, 100		
CDR1-BP391 -	390	F, G, J, K, M	BP	50, 100		
CDR1-BP431 -	430	F, G, J, K, M	BP	50, 100		
CDR1-BP471 -	470	F, G, J, K, M	BP	50, 100		
CDR1-BP511 -	510	F, G, J, K, M	BP	50, 100		
CDR1-BP561 -	560	F, G, J, K, M	BP	50, 100		
CDR1-BP621 -	620	F, G, J, K, M	BP	50, 100		
CDR1-BP681 -	680	F, G, J, K, M	BP	50, 100		
CDR1-BT751 -	750	F, G, J, K, M	BP	50, 100		
CDR1-BP821 -	820	F, G, J, K, M	BP	50, 100		
CDR1-BP911 -	910	F, G, J, K, M	BP	50, 100		
CDR1-BP102 -	1,000	F, G, J, K, M	BP	50, 100		

PART NUMBER EXAMPLE (How to Order)

Visit our website for the complete MIL-PRF-55681 Specification

CDR11	BP	101	A	F	M	S
Mil Style	Voltage Temperature Limits	Capacitance	Rated Voltage Code	Cap Tolerance Code	Termination Finish	Failure Rate Level
CDR11	BP = 0±30ppm/°C	3 Digit EIA Code	A = 50V B = 100V K = 150V	B = ± .10 pF < 10pF C = ± .25 pF < 10 pF D = ± .50 pF < 10 pF F = ± 1% G = ± 2% J = ± 5% K = ± 10% M = ± 20%	M = Palladium/Silver N = Silver-Nickel-Gold	CDR11 Only
CDR12	BG=90±20ppm/°C (not currently offered)				S = Solder Coated, Final with a Minimum of 4% Lead U = Base Metalization, Barrier Metal, Solder Coated (Tin/Lead Alloy with a Minimum of 4% Lead) Z = Base Metalization, Barrier Metal, Tinned (Tin/Lead Alloy with Minimum of 4% Lead)	CDR12 Only

DIMENSIONS — CDR11 AND CDR12 CAPACITORS

Consult factory for current qualification status.

Style Per MIL-C-55681	Length (L) Inches (mm)	Width (W) Inches (mm)	Thickness (T) Min Inches (mm)	Thickness (T) Max Inches (mm)	Metalization Band (M.B.) Inches (mm)
CDR11	0.055 ± 0.015 (1.40 ± 0.381)	0.055 ± 0.015 (1.40 ± 0.381)	0.020 (0.508)	0.057 (1.45)	0.010 – 0.005 + 0.010 (0.254 – 0.127 + 0.254)
CDR12	0.055 ± 0.025 (1.40 ± 0.635)	0.055 ± 0.015 (1.40 ± 0.381)	0.020 (0.508)	0.057 (1.45)	0.010 – 0.005 + 0.010 (0.254 – 0.127 + 0.254)

