

MIL-PRF-49467 Standard Profile

3000 Volts

MIL-PRF-49467	Capacitance	Cap. Tolerance	Characteristic	Case
M49467P03100J	10 pF	5%	BP	B
M49467P03100K	10 pF	10%	BP	B
M49467P03120J	12 pF	5%	BP	B
M49467P03120K	12 pF	10%	BP	B
M49467P03150J	15 pF	5%	BP	B
M49467P03150K	15 pF	10%	BP	B
M49467P03180J	18 pF	5%	BP	B
M49467P03180K	18 pF	10%	BP	B
M49467P03220J	22 pF	5%	BP	B
M49467P03220K	22 pF	10%	BP	B
M49467P03270J	27 pF	5%	BP	B
M49467P03270K	27 pF	10%	BP	B
M49467P03330J	33 pF	5%	BP	B
M49467P03330K	33 pF	10%	BP	B
M49467P03390J	39 pF	5%	BP	B
M49467P03390K	39 pF	10%	BP	B
M49467P03470J	47 pF	5%	BP	B
M49467P03470K	47 pF	10%	BP	B
M49467P03560J	56 pF	5%	BP	B
M49467P03560K	56 pF	10%	BP	B
M49467P03680J	68 pF	5%	BP	B
M49467P03680K	68 pF	10%	BP	B
M49467P03820J	82 pF	5%	BP	B
M49467P03820K	82 pF	10%	BP	B
M49467P03101J	100 pF	5%	BP	B
M49467P03101K	100 pF	10%	BP	B
M49467R03101K	100 pF	10%	BR	B
M49467R03101M	100 pF	20%	BR	B
M49467P03121J	120 pF	5%	BP	B
M49467P03121K	120 pF	10%	BP	B
M49467R03121K	120 pF	10%	BR	B
M49467R03121M	120 pF	20%	BR	B
M49467P03151J	150 pF	5%	BP	B
M49467P03151K	150 pF	10%	BP	B
M49467R03151K	150 pF	10%	BR	B
M49467R03151M	150 pF	20%	BR	B
M49467P03181J	180 pF	5%	BP	B
M49467P03181K	180 pF	10%	BP	B
M49467R03181K	180 pF	10%	BR	B

MIL-PRF-49467	Capacitance	Cap. Tolerance	Characteristic	Case
M49467Z03182J	1800 pF	10%	BZ	B
M49467Z03182K	1800 pF	20%	BZ	B
M49467P03222J	2200 pF	5%	BP	E
M49467P03222K	2200 pF	10%	BP	E
M49467R03222K	2200 pF	10%	BR	C
M49467R03222M	2200 pF	20%	BR	C
M49467Z03222K	2200 pF	10%	BZ	B
M49467Z03222M	2200 pF	20%	BZ	B
M49467P03272J	2700 pF	5%	BP	E
M49467P03272K	2700 pF	10%	BP	E
M49467R03272K	2700 pF	10%	BR	D
M49467R03272M	2700 pF	20%	BR	D
M49467Z03272K	2700 pF	10%	BZ	C
M49467Z03272M	2700 pF	20%	BZ	C
M49467P03332J	3300 pF	5%	BP	E
M49467P03332K	3300 pF	10%	BP	E
M49467R03332K	3300 pF	10%	BR	D
M49467R03332M	3300 pF	20%	BR	D
M49467Z03332K	3300 pF	10%	BZ	C
M49467Z03332M	3300 pF	20%	BZ	C
M49467P03392J	3900 pF	5%	BP	F
M49467P03392K	3900 pF	10%	BP	F
M49467R03392K	3900 pF	10%	BR	D
M49467R03392M	3900 pF	20%	BR	D
M49467Z03392K	3900 pF	10%	BZ	C
M49467Z03392M	3900 pF	20%	BZ	C
M49467P03472J	4700 pF	5%	BP	F
M49467P03472K	4700 pF	10%	BP	F
M49467R03472K	4700 pF	10%	BR	D
M49467R03472M	4700 pF	20%	BR	D
M49467P03562J	5600 pF	5%	BP	F
M49467P03562K	5600 pF	10%	BP	F
M49467R03562K	5600 pF	10%	BR	D
M49467R03562M	5600 pF	20%	BR	D
M49467P03682J	6800 pF	5%	BP	G
M49467P03682K	6800 pF	10%	BP	G
M49467R03682K	6800 pF	10%	BR	D
M49467R03682M	6800 pF	20%	BR	D
M49467R03822K	8200 pF	10%	BR	E



MIL-PRF-49467 Standard Profile

M49467R03181M	180 pF	20%	BR	B	M49467R03822M	8200 pF	20%	BR	E
M49467P03221J	220 pF	5%	BP	B	M49467Z03822K	8200 pF	10%	BZ	D
M49467P03221K	220 pF	10%	BP	B	M49467Z03822M	8200 pF	20%	BZ	D
M49467R03221K	220 pF	10%	BR	B	M49467R03103K	0.01 μF	10%	BR	E
M49467R03221M	220 pF	20%	BR	B	M49467R03103M	0.01 μF	20%	BR	E
M49467P03271J	270 pF	5%	BP	B	M49467Z03103K	0.01 μF	10%	BZ	D
M49467P03271K	270 pF	10%	BP	B	M49467Z03103M	0.01 μF	20%	BZ	D
M49467R03271K	270 pF	10%	BR	B	M49467R03123K	0.012 μF	10%	BR	E
M49467R03271M	270 pF	20%	BR	B	M49467R03123M	0.012 μF	20%	BR	E
M49467P03331J	330 pF	5%	BP	B	M49467Z03123K	0.012 μF	10%	BZ	D
M49467P03331K	330 pF	10%	BP	B	M49467Z03123M	0.012 μF	20%	BZ	D
M49467R03331K	330 pF	10%	BR	B	M49467R03153K	0.015 μF	10%	BR	F
M49467R03331M	330 pF	20%	BR	B	M49467R03153M	0.015 μF	20%	BR	F
M49467P03391J	390 pF	5%	BP	B	M49467Z03153K	0.015 μF	10%	BZ	E
M49467P03391K	390 pF	10%	BP	B	M49467Z03153M	0.015 μF	20%	BZ	E
M49467R03391K	390 pF	10%	BR	B	M49467R03183K	0.018 μF	10%	BR	F
M49467R03391M	390 pF	20%	BR	B	M49467R03183M	0.018 μF	20%	BR	F
M49467P03471J	470 pF	5%	BP	B	M49467Z03183K	0.018 μF	10%	BZ	E
M49467P03471K	470 pF	10%	BP	B	M49467Z03183M	0.018 μF	20%	BZ	E
M49467R03471K	470 pF	10%	BR	B	M49467R03223K	0.022 μF	10%	BR	F
M49467R03471M	470 pF	20%	BR	B	M49467R03223M	0.022 μF	20%	BR	F
M49467P03561J	560 pF	5%	BP	B	M49467Z03223K	0.022 μF	10%	BZ	E
M49467P03561K	560 pF	10%	BP	B	M49467Z03223M	0.022 μF	20%	BZ	E
M49467R03561K	560 pF	10%	BR	B	M49467R03273K	0.027 μF	10%	BR	G
M49467R03561M	560 pF	20%	BR	B	M49467R03273M	0.027 μF	20%	BR	G
M49467P0368J	680 pF	5%	BP	C	M49467Z03273K	0.027 μF	10%	BZ	F
M49467P03681K	680 pF	10%	BP	C	M49467Z03273M	0.027 μF	20%	BZ	F
M49467R03681K	680 pF	10%	BR	B	M49467R03333K	0.033 μF	10%	BR	G
M49467R03681M	680 pF	20%	BR	B	M49467R03333M	0.033 μF	20%	BR	G
M49467P03821J	820 pF	5%	BP	D	M49467Z03333K	0.033 μF	10%	BZ	F
M49467P03821K	820 pF	10%	BP	D	M49467Z03333M	0.033 μF	20%	BZ	F
M49467R03821K	820 pF	10%	BR	B	M49467R03393K	0.039 μF	10%	BR	G
M49467R03821M	820 pF	20%	BR	B	M49467R03393M	0.039 μF	20%	BR	G
M49467P03102J	1000 pF	5%	BP	D	M49467R03473K	0.047 μF	10%	BR	J
M49467P03102K	1000 pF	10%	BP	D	M49467R03473M	0.047 μF	20%	BR	J
M49467R03102K	1000 pF	10%	BR	B	M49467Z03473K	0.047 μF	10%	BZ	G
M49467R03102M	1000 pF	20%	BR	B	M49467Z03473M	0.047 μF	20%	BZ	G
M49467P03122J	1200 pF	5%	BP	D	M49467R03563K	0.056 μF	10%	BR	K
M49467P03122K	1200 pF	10%	BP	D	M49467R03563M	0.056 μF	20%	BR	K
M49467R03122K	1200 pF	10%	BR	B	M49467Z03563K	0.056 μF	10%	BZ	G
M49467R03122M	1200 pF	20%	BR	B	M49467Z03563M	0.056 μF	20%	BZ	G
M49467P03152J	1500 pF	5%	BP	D	M49467R03683K	0.068 μF	10%	BR	K
M49467P03152K	1500 pF	10%	BP	D	M49467R03683M	0.068 μF	20%	BR	K
M49467R03152K	1500 pF	10%	BR	B	M49467Z03683K	0.068 μF	10%	BZ	J
M49467R03152M	1500 pF	20%	BR	B	M49467Z03683M	0.068 μF	20%	BZ	J
M49467P03182J	1800 pF	5%	BP	E	M49467R03823K	0.082 μF	10%	BR	K
M49467P03182K	1800 pF	10%	BP	E	M49467R03823M	0.082 μF	20%	BR	K
M49467R03182K	1800 pF	10%	BR	C	M49467R03104K	0.1 μF	10%	BR	K
M49467R03182M	1800 pF	20%	BR	C	M49467R03104M	0.1 μF	20%	BR	K



MIL-PRF-49467 Standard Profile

Call Presidio for cross reference part numbers.

MIL-PRF-49467 PART NUMBER REFERENCE

<u>M49467</u>	<u>R</u>	<u>01</u>	<u>101</u>	<u>K</u>
Performance Specification Indicating MIL-PRF-49467	Characteristic (1.2.1.1)	Performance Specification Sheet Number Indicating MIL-PRF-49467/1	Capacitance Value (1.2.1.2)	Capacitance Tolerance (1.2.1.3)

