

MIL-PRF-49467 Standard Profile

5000 Volts

MIL-PRF-49467	Capacitance	Cap. Tolerance	Characteristic	Case
M49467P05100J	10 pF	5%	BP	M
M49467P05100K	10 pF	10%	BP	M
M49467P05120J	12 pF	5%	BP	M
M49467P05120K	12 pF	10%	BP	M
M49467P05150J	15 pF	5%	BP	M
M49467P05150K	15 pF	10%	BP	M
M49467P05180J	18 pF	5%	BP	M
M49467P05180K	18 pF	10%	BP	M
M49467P05220J	22 pF	5%	BP	M
M49467P05220K	22 pF	10%	BP	M
M49467P05270J	27 pF	5%	BP	M
M49467P05270K	27 pF	10%	BP	M
M49467P05330J	33 pF	5%	BP	M
M49467P05330K	33 pF	10%	BP	M
M49467P05390J	39 pF	5%	BP	M
M49467P05390K	39 pF	10%	BP	M
M49467P05470J	47 pF	5%	BP	M
M49467P05470K	47 pF	10%	BP	M
M49467P05560J	56 pF	5%	BP	M
M49467P05560K	56 pF	10%	BP	M
M49467P05680J	68 pF	5%	BP	M
M49467P05680K	68 pF	10%	BP	M
M49467P05820J	82 pF	5%	BP	M
M49467P05820K	82 pF	10%	BP	M
M49467P05101J	100 pF	5%	BP	M
M49467P05101K	100 pF	10%	BP	M
M49467R05101J	100 pF	5%	BR	M
M49467R05101K	100 pF	10%	BR	M
M49467P05121J	120 pF	5%	BP	M
M49467P05121K	120 pF	10%	BP	M
M49467R05121J	120 pF	5%	BR	M
M49467R05121K	120 pF	10%	BR	M
M49467P05151J	150 pF	5%	BP	M
M49467P05151K	150 pF	10%	BP	M
M49467R05151K	150 pF	10%	BR	M
M49467R05151M	150 pF	20%	BR	M
M49467P05181J	180 pF	5%	BP	M
M49467P05181K	180 pF	10%	BP	M
M49467R05181K	180 pF	10%	BR	M

MIL-PRF-49467	Capacitance	Cap. Tolerance	Characteristic	Case
M49467P05122K	1200 pF	10%	BP	F
M49467R05122K	1200 pF	10%	BR	E
M49467R05122M	1200 pF	20%	BR	E
M49467P05152J	1500 pF	5%	BP	F
M49467P05152K	1500 pF	10%	BP	F
M49467R05152K	1500 pF	10%	BR	E
M49467R05152M	1500 pF	20%	BR	E
M49467P05182J	1800 pF	5%	BP	F
M49467P05182K	1800 pF	10%	BP	F
M49467R05182K	1800 pF	10%	BR	E
M49467R05182M	1800 pF	20%	BR	E
M49467P05222J	2200 pF	5%	BP	G
M49467P05222K	2200 pF	10%	BP	G
M49467R05222K	2200 pF	10%	BR	E
M49467R05222M	2200 pF	20%	BR	E
M49467P05272J	2700 pF	5%	BP	G
M49467P05272K	2700 pF	10%	BP	G
M49467R05272K	2700 pF	10%	BR	F
M49467R05272M	2700 pF	20%	BR	F
M49467Z05272K	2700 pF	10%	BZ	E
M49467Z05272M	2700 pF	20%	BZ	E
M49467P05332J	3300 pF	5%	BP	G
M49467P05332K	3300 pF	10%	BP	G
M49467R05332K	3300 pF	10%	BR	F
M49467R05332M	3300 pF	20%	BR	F
M49467Z05332K	3300 pF	10%	BZ	E
M49467Z05332M	3300 pF	20%	BZ	E
M49467P05392J	3900 pF	5%	BP	K
M49467P05392K	3900 pF	10%	BP	K
M49467R05392K	3900 pF	10%	BR	F
M49467R05392M	3900 pF	20%	BR	F
M49467Z05392K	3900 pF	10%	BZ	E
M49467Z05392M	3900 pF	20%	BZ	E
M49467P05472J	4700 pF	5%	BP	K
M49467P05472K	4700 pF	10%	BP	K
M49467R05472K	4700 pF	10%	BR	F
M49467R05472M	4700 pF	20%	BR	F
M49467Z05472K	4700 pF	10%	BZ	E
M49467Z05472M	4700 pF	20%	BZ	E



MIL-PRF-49467 Standard Profile

M49467R05181M	180 pF	20%	BR	M	M49467R05562J	5600 pF	5%	BP	K
M49467P05221J	220 pF	5%	BP	M	M49467R05562K	5600 pF	10%	BP	K
M49467P05221K	220 pF	10%	BP	M	M49467R05562K	5600 pF	10%	BR	F
M49467R05221K	220 pF	10%	BR	M	M49467R05562M	5600 pF	20%	BR	F
M49467R05221M	220 pF	20%	BR	M	M49467Z05562K	5600 pF	10%	BZ	F
M49467P05271J	270 pF	5%	BP	M	M49467Z05562M	5600 pF	20%	BZ	F
M49467P05271K	270 pF	10%	BP	M	M49467R0568K	6800 pF	10%	BR	G
M49467R05271K	270 pF	10%	BR	M	M49467R05682M	6800 pF	20%	BR	G
M49467R05271M	270 pF	20%	BR	M	M49467Z05682K	6800 pF	10%	BZ	F
M49467P05331J	330 pF	5%	BP	E	M49467Z05682M	6800 pF	20%	BZ	F
M49467P05331K	330 pF	10%	BP	E	M49467R05822K	8200 pF	10%	BR	G
M49467R0533K	330 pF	10%	BR	M	M49467R05822M	8200 pF	20%	BR	G
M49467R05331M	330 pF	20%	BR	M	M49467Z05822K	8200 pF	10%	BZ	G
M49467P05391J	390 pF	5%	BP	E	M49467Z05822M	8200 pF	20%	BZ	G
M49467P05391K	390 pF	10%	BP	E	M49467R05103K	0.01 μF	10%	BR	J
M49467R05391K	390 pF	10%	BR	M	M49467R05103M	0.01 μF	20%	BR	J
M49467R05391M	390 pF	20%	BR	M	M49467Z05103K	0.01 μF	10%	BZ	G
M49467P05471J	470 pF	5%	BP	F	M49467Z05103M	0.01 μF	20%	BZ	G
M49467P05471K	470 pF	10%	BP	F	M49467R05123K	0.012 μF	10%	BR	J
M49467R05471K	470 pF	10%	BR	M	M49467R05123M	0.012 μF	20%	BR	J
M49467R05471M	470 pF	20%	BR	M	M49467Z05123K	0.012 μF	10%	BZ	G
M49467P05561J	560 pF	5%	BP	F	M49467Z05123M	0.012 μF	20%	BZ	G
M49467P05561K	560 pF	10%	BP	F	M49467R05153K	0.015 μF	10%	BR	J
M49467R05561K	560 pF	10%	BR	M	M49467R05153M	0.015 μF	20%	BR	J
M49467R05561M	560 pF	20%	BR	M	M49467Z05153K	0.015 μF	10%	BZ	J
M49467P05681J	680 pF	5%	BP	F	M49467Z05153M	0.015 μF	20%	BZ	J
M49467P05681K	680 pF	10%	BP	F	M49467R05183K	0.018 μF	10%	BR	K
M49467R05681K	680 pF	10%	BR	E	M49467R05183M	0.018 μF	20%	BR	K
M49467R05681M	680 pF	20%	BR	E	M49467Z05183K	0.018 μF	10%	BZ	J
M49467P05821J	820 pF	5%	BP	F	M49467Z05183M	0.018 μF	20%	BZ	J
M49467P05821K	820 pF	10%	BP	F	M49467R05223K	0.022 μF	10%	BR	K
M49467R05821K	820 pF	10%	BR	E	M49467R05223M	0.022 μF	20%	BR	K
M49467R05821M	820 pF	20%	BR	E	M49467Z05223K	0.022 μF	10%	BZ	K
M49467P05102J	1000 pF	5%	BP	F	M49467Z05223M	0.022 μF	20%	BZ	K
M49467P05102K	1000 pF	10%	BP	F	M49467Z05273K	0.027 μF	10%	BZ	K
M49467R05102K	1000 pF	10%	BR	E	M49467Z05273M	0.027 μF	20%	BZ	K
M49467R05102M	1000 pF	20%	BR	E	M49467Z05333K	0.033 μF	10%	BZ	K
M49467P05122J	1200 pF	5%	BP	F	M49467Z05333M	0.033 μF	20%	BZ	K

Call Presidio for cross reference part numbers.

MIL-PRF-49467 PART NUMBER REFERENCE

M49467	R	01	101	K
Performance Specification Indicating MIL-PRF-49467	Characteristic (1.2.1.1)	Performance Specification Sheet Number Indicating MIL-PRF-49467/1	Capacitance Value (1.2.1.2)	Capacitance Tolerance (1.2.1.3)



PRESIDIO COMPONENTS, INC.

7169 Construction Court, San Diego, CA 92121 USA • Tel: 858-578-9390 • Fax: 800-538-3880 or 858-578-6225
Web: www.presidiocomponents.com • Email: info@presidiocomponents.com